

弹性支撑简介



技术参数
采用材料：钢&铝
产品功能：① 具备弹簧减震、高度补偿作用
② 采用侧面安装，有效降低安装高度
③ 弹簧内置无行程限位且产品有防转功能
适用范围：① 适用于周期短，搬运速度快，重载工况
② 适用于拆垛工位

产品型号	S (mm)	L (mm)	弹簧力/(N)		A	B	重量 (kg)
			Fmax	Fmin			
DT-GS-TP-19-NPT3/8-NPT1/4	19.0	110.5	19.2	6.4	NPT3/8	NPT1/4	0.28
DT-GS-TP-25-G1/4-G3/8	25.0	111.0	18.7	6.4	G1/4	G1/4	0.28
DT-GS-TP-25-G3/8-G1/4						G3/8	0.27
DT-GS-TP-25-G3/8-G3/8					G3/8	G1/4	0.28
DT-GS-TP-25-G1/4-G1/4						G3/8	0.27
DT-GS-TP-50-G1/4-G1/4	50.0	172.0	20.2	2.8	G1/4	G1/4	0.36
DT-GS-TP-50-G1/4-G3/8						G3/8	0.35
DT-GS-TP-50-G3/8-G1/4					G3/8	G1/4	0.36
DT-GS-TP-50-G3/8-G3/8						G3/8	0.35
DT-GS-TP-75-G1/4-G1/4	75.0	216.0	22.4	2.7	G1/4	G1/4	0.42
DT-GS-TP-75-G1/4-G3/8						G3/8	0.41
DT-GS-TP-75-G3/8-G1/4					G3/8	G1/4	0.42
DT-GS-TP-75-G3/8-G3/8						G3/8	0.41
DT-GS-TP-100-G1/4-G1/4	100.0	275.5	21.4	1.0	G1/4	G1/4	0.59
DT-GS-TP-100-G1/4-G3/8						G3/8	0.58
DT-GS-TP-100-G3/8-G1/4					G3/8	G1/4	0.59
DT-GS-TP-100-G3/8-G3/8						G3/8	0.58

◆ 弹性支撑依据客户需求，特殊行程可定制。

应用范例

